



# JPU

JPU Reinigungsprodukte GmbH



## M35 Blue Scrubbing

With their rough surface, the Blue Scrubbing Janex Super Pads are a bit softer than the green pads. They are well suited for the dry care film renovation as well as for care film cleaning on resilient floor coverings such as linoleum, PVC or rubber. The abrasive qualities of the Blue Pad are somewhere between the properties of the green and red pad and are strong enough so that the old care film is reliably removed, without damaging the underlying layer.

## Janex Super Pads



### Use

Use with a neutral floor cleaning solution to remove old soiled floor finish layers. This product is also used to scrub soiled hard surface floors such as concrete when used with appropriate cleaning chemicals. Ideal for use on machine speeds up to 350 rpm.

### Construction

The Blue Scrubbing Pad is constructed of polyester fibers along with synthetic adhesives that will not be notably affected by water or cleaners used in standard floor maintenance. The abrasives used in this product are synthetic. This pad has been designed for use on both sides. Thickness 24 mm.

### Directions for Use

Dust mop or sweep floors prior to scrubbing. Use pad until soiled finish is removed from floor. Pick up cleaning solution with a mop, wet vacuum or automatic scrubber. Rinse floor and let dry prior to re-coating or opening to traffic. Polish with JPU polishing/burnishing pad to achieve a high gloss finish.

### Product Care

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.

### Description

The Blue Cleaner Pad is constructed of polyester fibers in a semi open texture non-woven fabrication and is designed for medium scrubbing. Abrasive particles are dispersed throughout and bonded to the non-woven construction with a durable adhesive.



### Full Cycle® Product

**Note:** Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results. Please contact JPU with any questions or concerns.