



M04 Black Stripping

Black Stripping & Brown Stripping: The hardest Janex Super Pads are ideal for all intensive cleaning work such as the thorough removal of dirt layers on wooden floors. The abrasive particle concentration is high, so that coatings such as wax can be removed – on softer floors it is advisable to first check for scratch resistance before using these pads. We recommend less hard cleaning pads for sensitive / soft woods.



M36 Brown Stripping

Tan Thin: The abrasive effect of the brown pads is significantly reduced compared to the black stripping pads. They can be used for routine cleaning on PVC and synthetic resin floors as well as on wood, parquet and cork floors. The suitability here is for wet and dry cleaning alike. Again: check for scratch resistance and switch to a softer pad for very sensitive floors.



M31 Tan Thin

Green Scrubbing: With a medium degree of hardness, these pads are mainly suitable for use as a massage pad; various basic floor treatments or the introduction of colour oils can be efficiently worked into wooden surfaces with green scrubbing pads. Also suitable for easy basic cleaning (removal of footprints on all types of floors). Green pads offer the right compromise if the use of harder pads is not appropriate and softer pads are not efficient enough.



M30 Green Scrubbing

Blue Scrubbing: With their very grippy, rough surface, the blue pads are softer than the green pads. They are well suited for the surface renovation and surface cleaning of elastic floor coverings such as linoleum, PVC or rubber. The abrasive qualities of the Blue Scrubbing lie between the green and red pads and are also strong enough that the old care film is reliably removed without damaging the floor underneath.



M35 Blue Scrubbing

Red Spray Buff: The softest of the classic cleaning pads. They are suitable for the gentle cleaning of even the most sensitive floors, for which the harder pads are no option. Despite the rather light cleaning effect, the red pads are efficient enough to remove dirt.



M34 Red Spray Buff

Tan Polishing: The Tan Pads are particularly well suited for pre-polishing and applying care products such as hard floor wax or care pastes and oils. Grippier than the White Polishing pads, which have similar properties, they can also be used for light cleaning work, such as wet wiping.



M31 Tan Polishing

White Polishing: These pads are completely free of abrasives. As non-abrasive polishing pads, they are designed for final polishing. The softest pads in this Super Pad category is ideal for processing all types of care oils, especially on sensitive and splinter-prone softwood floors. The strengths of the White Polishing pads are clearly on the care product application. The reduced degree of hardness has no negative impact on tool life. For cleaning purposes however, we advise to use a harder pad.



M44 White Polishing



JPU

JPU Reinigungsprodukte GmbH



M32 Black Stripping

The hardest Janex Super Pads are best used for all intense cleaning works such as the thorough removal of dirt layers on wooden floors. The grinding particle concentration is high so that surface layers such as wax layers can be removed – examine softer floors for scratch resistance before use. Sensitive types of wood should be treated with softer pads.

Janex Super Pads



Use

Use with water based floor stripping solution to remove worn and soiled floor finishes or sealers. May also used to clean heavily soiled hard surface floors, such as concrete, when used with proper cleaning solutions. For use on standard electric floor machines or automatic scrubbers. Ideal for use on machines speeds up to 350 rpm.

Description

The Black Stripping pad is constructed of polyester fibers in an open texture non-woven fabrication. Abrasive particles are distributed throughout the pad and adhered to the non-woven construction with a sturdy adhesive. Thickness 24 mm.

Construction

The Black Stripping is constructed of polyester fibers along with synthetic adhesives that will not be notably affected by water or cleaners used in standard floor maintenance. The abrasives used in this product are synthetic. This pad has been designed for use on both sides

Directions for Use

Dust mop or sweep floors prior to stripping. Use pad until soil and finish are removed from floor. Pick up stripping or cleaning solution with a mop, wet vacuum or automatic scrubber. Rinse floor and let dry prior to re-coating or opening to traffic.

Product Care

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.



Full Cycle® Product

Note: Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results. Please contact JPU with any questions or concerns.



M36 Brown Stripping

The abrasive effect of the brown pads is significantly reduced compared to the black pads, so that they can be safely used on PVC and synthetic resin floors as well as on wood, parquet and cork floors for maintenance cleaning. The suitability is here for wet and dry cleaning alike. However, it still applies here: Check for scratch resistance and switch to a softer pad on very sensitive floors.

Janex Super Pads



Use

Use with water based floor stripping solution to remove worn and soiled floor finishes or sealers. May also used to clean heavily soiled hard surface floors, such as concrete, when used with proper cleaning solutions. For use on standard electric floor machines or automatic scrubbers. Ideal for use on machines speeds up to 350 rpm.

Construction

The Brown Stripping Pad is constructed of polyester fibers along with synthetic adhesives that will not be notably affected by water or cleaners used in standard floor maintenance. The abrasives used in this product are synthetic. This pad has been designed for use on both sides. Thickness 24 mm.

Directions for Use

Dust mop or sweep floors prior to stripping. Use pad until soil and finish are removed from floor. Pick up stripping or cleaning solution with a mop, wet vacuum or automatic scrubber. Rinse floor and let dry prior to re-coating or opening to traffic.

Product Care

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing..

Description

The Brown Stripping Pad is constructed of polyester fibers in a semi open texture non-woven fabrication and is designed for medium duty stripping. Abrasive particles are distributed throughout and adhered to the non-woven construction with a sturdy adhesive. This product is designed specifically for customers who want a more dense non-woven pad.



Full Cycle® Product

Note: Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results. Please contact JPU with any questions or concerns.



M30 Green Scrubbing

With a medium degree of hardness, the Green Scrubbing Janex Super Pads are massage pads. Best suited for various basic treatments as the application of colouroils which can be efficiently applied to wood surfaces. Also suitable for basic cleaning (removal of traces of all types of soil). Green pads are the perfect compromise when the use of harder pads is not appropriate and softer pads are not quite efficient enough.

Janex Super Pads



Use

Use with a cleaning solution to scrub hard floor surfaces. This pad will aggressively remove dirt and scuff marks from heavily soiled floors. It is also designed for light stripping. For use on standard electric floor machines or automatic scrubbers. Ideal for use on machines speeds up to 350 rpm.

Description

The Green Scrubbing pad is constructed of polyester fibers in a semi open texture non-woven fabrication and is designed for deep scrubbing. Abrasive particles are dispersed throughout and bonded to the non-woven construction with a durable adhesive. Thickness 24 mm.

Directions for Use

Sweep or dust mop floors prior to scrubbing. Scrub floor using a standard electric automatic scrubber. Remove cleaning solution with a damp mop or wet vacuum if using a standard electric machine. Rinse floor and let dry prior to re-coating.

Product Care

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.

Construction

The Green Scrubbing pad is constructed of polyester fibers along with synthetic adhesives that will not be notably affected by water or cleaners used in standard floor maintenance. The abrasives used in this product are synthetic. This pad has been designed for use on both sides



Full Cycle® Product

Note: Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results. Please contact JPU with any questions or concerns.



M35 Blue Scrubbing

With their rough surface, the Blue Scrubbing Janex Super Pads are a bit softer than the green pads. They are well suited for the dry care film renovation as well as for care film cleaning on resilient floor coverings such as linoleum, PVC or rubber. The abrasive qualities of the Blue Pad are somewhere between the properties of the green and red pad and are strong enough so that the old care film is reliably removed, without damaging the underlying layer.

Janex Super Pads



Use

Use with a neutral floor cleaning solution to remove old soiled floor finish layers. This product is also used to scrub soiled hard surface floors such as concrete when used with appropriate cleaning chemicals. Ideal for use on machine speeds up to 350 rpm.

Construction

The Blue Scrubbing Pad is constructed of polyester fibers along with synthetic adhesives that will not be notably affected by water or cleaners used in standard floor maintenance. The abrasives used in this product are synthetic. This pad has been designed for use on both sides. Thickness 24 mm.

Directions for Use

Dust mop or sweep floors prior to scrubbing. Use pad until soiled finish is removed from floor. Pick up cleaning solution with a mop, wet vacuum or automatic scrubber. Rinse floor and let dry prior to re-coating or opening to traffic. Polish with JPU polishing/burnishing pad to achieve a high gloss finish.

Product Care

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.

Description

The Blue Cleaner Pad is constructed of polyester fibers in a semi open texture non-woven fabrication and is designed for medium scrubbing. Abrasive particles are dispersed throughout and bonded to the non-woven construction with a durable adhesive.



Full Cycle® Product

Note: Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results. Please contact JPU with any questions or concerns.



M34 Red Spray Buff

The softest of the classic cleaning pads the Red Spray Buff Janex Super Pad are best suited for the gentle cleaning of even the most sensitive floors, for which the harder pads are no longer suitable. Despite the rather light cleaning effect, the red pads are efficient enough to handle intensive soiling spots.

Janex Super Pads



Use

This pad is designed for light duty cleaning and buffing. It will remove light scuff marks and dirt while producing a high gloss shine. For use with standard electric floor machines, orbital scrubbers and automatic scrubbers. Ideal for use on machines speeds up to 800 rpm.

Construction

The Red Spray Buff Super Pad is made of 100% recycled polyester fibers and water based resins. This pad has been designed for use on both sides. Thickness 26 mm.

Directions for Use

Dust mop or sweep floors prior to cleaning or buffing. Damp mopping may be necessary if floors are heavily soiled. A spray cleaning solution may be use. Buff until glossy.

Product Care

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.

Description

The Red Spray Buff Super Pad is used for light cleaning and buffing. It is constructed of polyester fibers in a semi open textured, non-woven pattern bonded with a durable adhesive.



Full Cycle® Product

Note: Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results. Please contact JPU with any questions or concerns.



M31 Tan Polishing

The abrasive effect of the Tan Polishing pads is significantly reduced compared to the black pads, so that they can be safely used on PVC and synthetic resin floors as well as on wood, parquet and cork floors for maintenance cleaning. The suitability is here for wet and dry cleaning alike. However, it still applies here: Check for scratch resistance and switch to a softer pad on very sensitive floors.

Janex Super Pads



Use

This pad is designed for light duty cleaning and buffing. It will remove light scuff marks and dirt while producing a high gloss shine. For use with standard electric floor machines, orbital scrubbers and automatic scrubbers. Ideal for use on machines speeds up to 800 rpm.

Construction

The Tan Polishing Pad is made of 100% recycled polyester fibers and water based resins. This pad has been designed for use on both sides. Thickness 26 mm.

Directions for Use

Dust mop or sweep floors prior to cleaning or buffing. Damp mopping may be necessary if floors are heavily soiled. A spray cleaning solution may be use. Buff until glossy.

Product Care

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.

Description

The Tan Polishing pad is a floor maintenance pad used for light cleaning and buffing. It is constructed of polyester fibers in a dense textured, non-woven pattern bonded with a sturdy adhesive.



Full Cycle® Product

Note: Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results. Please contact JPU with any questions or concerns.



JPU

JPU Reinigungsprodukte GmbH



M33 White Polishing

The white Janex Super Pads are completely free of abrasives. As non-abrasive polishing pads, they are designed for final polishing. The softest pad in this Super Pad category and great for processing all types of floor maintenance oils, especially on sensitive and chip-prone softwood floors. The strengths of the white pads are clearly on the care application. The reduced degree of hardness does not have a negative effect on the service life. For cleaning purposes, use a harder pad.

Janex Super Pads



Use

This extra fine pad has been designed for polishing clean, dry floors. Use dry or with restorative chemicals, to produce a wet look gloss to newly finished floors. For use with standard electric floor machines, ultra high speed machines, orbital scrubbers and automatic scrubbers. Ideal for use on machines speeds up to 3000 rpm.

Construction

The White Polishing Pad is made of 100% recycled polyester fibers and water based resins. This product is made to be reversible. Thickness 26 mm.

Directions for Use

Dust mop or sweep floors prior to polishing. For use on a clean, dry floor. May be used dry or with restorative chemicals.

Product Care

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.

Description

The White Polishing floor maintenance pad is made of polyester fibers in a dense textured, non-woven pattern, bonded with a sturdy adhesive.



Full Cycle® Product

Note: Due to the intrinsic properties of the material and variable conditions of use, there may be slight variations in the specifications and results. Please contact JPU with any questions or concerns.